

## Cargo Handling Equipment

Type	Units	Capacity
Ship to Shore Gantry Cranes (LIEBHERR). Rail-mounted, Post Panamax sized cranes	2	Safe Working Load (S.W.L.) under telescopic spreader: 40 tonnes (Single Lift), 50 tonnes (Twin Lift).
Rubber Tyred Gantry Cranes (KONECRANE)	6	5 high; 7 wide; safe working load 50 tonnes.
Mobile Harbour Crane (GOTTWALD)	2	MHC280 maximum capacity - 100 tonnes MHC6507 maximum capacity – 125 tonnes These cranes are versatile for handling bulk, break-bulk and containerized cargo.
Reach Stackers (four and five high)	5	Four and five high
Forklifts	13	3 to 30 tonnes
Empty Container Handler (four high)	3	Comprises: <ul style="list-style-type: none"> <li>• 2 ECH-Kalmar</li> <li>• 1 ECH-Terex</li> </ul>
Tractor Trucks	22	Comprises: <ul style="list-style-type: none"> <li>• 8 Capacity</li> <li>• 14 Kalmar Ottawa</li> </ul>
Standby Generator	1	Live reefer containers, power supply
Trailers	29	40 feet and 45 feet
Ariel Work Platforms (Man lifts)	2	Genie S85 - maximum reach 85ft JLG 1850 SJ - maximum reach 185 ft

September 19, 2024  
Engineering and Maintenance Department.